MERCURY AIR 20

PREMIUM RUBBER 20 BAR AIR ISO2398-4A



Product Information

Order Ref:	RAH-SIZE MM
Tube:	SYNTHETIC RUBBER INNER
Reinforcement:	HIGH TENSILE SYNTHETIC TEXTILE
Cover:	ABRASION, OZONE AND WEATHER RESISTANT SMOOTH NATURAL AND SYNTHETIC RUBBER
Application:	MEDIUM DUTY SERVICE FOR AIR AND PNEUMATIC TOOLS SPECIFICALLY IN MINES, QUARRIES AND CONSTRUCTION
Specification:	TS 745 / EN ISO 2398 TYPE 4/A

	ID	OD	WP	WP	BP	BP	BR	W/A	COIL
inch	mm	mm	BAR	PSI	BAR	PSI	mm	gr/m	m
1/4	6	13	20	290	60	870	60	130	25/100
5/16	8	16	20	290	60	928	80	190	25/100
3/8	10	18	20	290	60	870	100	230	25/50/100
1/2	13	22	20	290	60	870	130	333	25/50/100
3/4	19	30	20	290	60	928	190	580	25/50
1	25	36	20	290	60	870	250	730	25/50

-40ºC to +70ºC

Branding: MERCURY 20 AIR/WP 20BAR ISO2398 4A-SIZE QTR/YR
Colour : BLACK

We use cookies to give you the best experience on our site. By using our site you accept our **Privacy Policy**Accept & Close