


TEXAS 10 S&D

10 BAR OIL SUCTION AND DELIVERY



Product Information

Order Ref:	OSH-SIZE MM
Tube:	OIL AND PETROL RESISTANT, CONDUCTIVE SYNTHETIC NITRILE BLACK RUBBER
Reinforcement:	HIGH TENSILE SYNTHETIC TEXTILE, STEEL WIRE HELIX AND ANTI-STATIC COPPER WIRE
Cover:	OIL, WEATHER, OZONE, ABRASION AND SEA WATER RESISTANT, SPECIAL SYNTHETIC RUBBER
Application:	SUCTION & DELIVERY FOR FILLING AND DISCHARGING TANKS, PETROL TANKERS AND SHIPS WITH UNLEADED FUELS (EN228:2017) WITH AN AROMATIC CONTENT OF COMPONENTS 50% MAX

										
inch	mm	mm	BAR	PSI	BAR	PSI	BAR	mm	gr/m	m
3/4	19	30	10	145	30	450	-0.92	90	600	10/20/40
1	25.4	35	10	145	30	450	-0.92	110	650	10/20/40
1 1/4	32	42	10	145	30	450	-0.92	140	835	10/20/40
1 1/2	38	48	10	145	30	450	-0.92	170	1050	10/20/40
1 3/4	44.5	55	10	145	30	450	-0.92	210	1290	10/40
2	50.8	61	10	145	30	450	-0.92	250	1495	10/20/40/61
2 1/4	57	69	10	145	30	450	-0.92	275	1885	10/40

23/8	60	72	10	145	30	450	-0.92	295	1990	10/40
21/2	63.5	74	10	145	30	450	-0.92	310	2010	10/40
3	76.2	87	10	145	30	450	-0.92	380	2337	10/40
31/2	90	102	10	145	30	450	-0.92	450	2940	10/40
4	101.6	115	10	145	30	450	-0.92	510	3440	10/40
5	127	145	10	145	30	450	-0.92	650	6195	10/40
6	152	170	10	145	30	450	-0.92	752	7050	10/40



-40°C to +90°C (+100°C when used with oil) Branding: TEXAS 10 - OIL SUCTION AND DELIVERY W.P. 10 BAR
Colour : BLACK

We use cookies to give you the best experience on our site. By using our site you accept our [Privacy Policy](#) [Accept & Close](#)