FIRE LAYFLAT TYPE 3

LAYFLAT FIRE FIGHTING HOSE TYPE 3



Product Information

Order Ref:	TYPE3-SIZE MM
Cover:	RUBBERISED LINING AND COVER - VERY HIGH GRADE NBR/PVC RUBBER COMPOUND. ADDITIVES IN THE COMPOUND GIVE O/S RESISTANCE TO AGEING AND OZONE
Application:	REFINERIES, CHEMICAL WORKS, MILITARY, AIRPORT FIRE SERVICES, INDUSTRIAL AND MUNICIPAL FIRE BRIGADES
Specification:	DIN 14811 WITH STORZ FITTINGS DIA 25-76MM MWP 16 BAR - BS6391 - 2009 WITH BRITISH INSTANTANEOUS COUPLINGS DIA 38-76MM MWP 15 BAR DIA 89MM MWP 12 BAR

	ID	Wall Thickness	BP	BR	W/A	COIL
inch	**mm**	**mm**	**BAR**	**mm**	**gr/m**	**m**
13/4	45	2,30	50	60	340	15/18/20/23/30
2	52	2,50	50	60	400	15/18/20/23/30
21/2	64	2,60	50	60	570	15/18/20/23/30
23/4	70	2,80	50	60	600	15/18/20/23/30
3	75	2,90	50	80	650	15/18/20/23/30

Standard colour is red but others available.

HOSE CAN BE SUPPLIED WITH COUPLINGS.

-20°C TO + 80°C

Branding: NONE
Colour : RED

We use cookies to give you the best experience on our site. By using our site you accept our **Privacy Policy**Accept & Close