










# MERCURY AIR 20 YELLOW

PREMIUM RUBBER 20 BAR AIR YELLOW



## Product Information

Order Ref:	RAY-SIZE MM
Tube:	OIL RESISTANT NATURAL AND SYNTHETIC RUBBER
Reinforcement:	HIGH TENSILE SYNTHETIC TEXTILE
Cover:	ABRASION, OZONE AND WEATHER RESISTANT SMOOTH NATURAL AND SYNTHETIC RUBBER
Application:	MEDIUM DUTY SERVICE FOR AIR AND PNEUMATIC TOOLS SPECIALLY IN MINES, QUARRIES AND CONSTRUCTION
Specification:	TS 745 / EN ISO 2398 TYPE 4/A

									
inch	mm	mm	BAR	PSI	BAR	PSI	mm	gr/m	m
3/8	10	18	20	290	60	870	100	220	100
1/2	13	21	20	290	60	870	130	270	100
3/4	19	30	20	290	60	928	190	570	30 / 60
1	25	37	20	290	60	870	250	800	30 / 60



-25°C to +70°C

Branding: MERCURY 20 AIR - WP 20BAR ISO2398 4A-SIZE QTR/YR  
Colour : YELLOW

We use cookies to give you the best experience on our site. By using our site you accept our [Privacy Policy](#) [Accept & Close](#)