TEXAS 10 FLEXI

10 BAR CORRUGATED SUCTION AND DELIVERY HOSE



Product Information

Order Ref:	COS-SIZE-MM
Tube:	OIL AND PETROL RESISTANT BLACK NBR
Reinforcement:	HIGH TENSILE SYNTHETIC TEXTILE STEEL WIRE HELIX AND ANTISTATIC COPPER WIRE
Cover:	OIL, WEATHER, OZONE ABRASION AND SEA WATER RESISTANT, CORRUGATED SPECIAL SYNTHETIC RUBBER
Application:	FOR SUCTION AND DISCHARGE OF PETROLEUM PRODUCTS WITH AROMATIC CONTENT UP TO 50%

	ID	OD	WP	WP	BP	BP	W/A	BR	VACUUM	COIL
inch	**mm**	**mm**	**BAR**	**PSI**	**BAR**	**PSI**	**gr/m**	**mm**	**m.H²O**	**m**
11/4	32	42	10	145	30	435	826	120	-0.92	40
11/2	38	48	10	145	30	435	965	140	-0.92	40
2	51	63	10	145	30	435	1697	190	-0.92	40

-30ºC /+70ºC

Branding: NONE
Colour : BLACK

We use cookies to give you the best experience on our site. By using our site you accept our **Privacy Policy**Accept & Close